

DIGITAL ELCB TESTER



CE

6220 EL

FEATURES

- Microprocessor technology ensures high performance accuracy and reliability.
- Fully programmable via tactile key pad.
- Direct readout of disconnection, time or current.
- Voltage measured during test.
- Housed in a heavy duty carry case.
- Suitable for all industrial, mining and domestic environments.
- Display can be customized for special orders.
- Indicate Voltage and Trip Current/Time.
- Use binary principle.
- True resistor switching.
- IEC 1010-1 CAT III

SPECIFICATIONS

Rated Tripping Current at 317V	1000mA (2000mA on special orders)
Lowest Resolution	1mA
System Voltage	230 / 380 / 550V / 50Hz
Maximum Trip Time	99.99s
Highest Resolution	10ms
Typical Accuracy	
Rated Trip Current	±1%rdg ±2dgt
Voltage Range	±1%rdg ±1dgt
Trip Time	±1%rdg ±2dgt
Operating-Temperature	0°C ~ 40°C
Operating-Humidity	80% Max. relative humidity
Dimensions	330(L) x 260(W) x 160(D)mm
Weight	Approx. 3.7kg (battery included)
Power Source	1.5V "C" x 8 Alkaline Batteries
Accessories	Test leads Instruction manual Battery



STANDARD ELECTRIC WORKS CO., LTD.

NO.106, SU WEI ROAD, PAN CHIAO, TAIPEI HSIEN, TAIWAN, R.O.C.

TEL: 886-2-22563125 FAX: 886-2-22556352 886-2-82573518

http://www.sew.com.tw e-mail: sales@sew.com.tw e-mail: sew@ms10.hinet.net